



ELITE MODEL

LIQUID MANURE SPREADER



LITRES	4500	7000	9000	12000	15000
U.S. GALLON	1200	1800	2400	3000	4000
CAN. GALLON	1000	1500	2000	2500	3300
Tractor size	60	75	90	100	130

ALL SIZES and H.P. ARE APPROXIMATE

COMMITTED TO QUALITY YOU CAN DEPEND ON!

- 10 Year **WARRANTY** Against Tank Rust Out
- 5 Year Axle And Undercarriage **WARRANTY**
- Adjustable Axle For Best Weight
- Prime High Carbon Heavy Gauge Steel Tank
- Fully Lined Inside Against Rust
- All Seams Welded Inside And Out
- Flanged Ends & Full Baffle For Strength
- Parts Book And Owners Manual Supplied
- Constant Velocity P.T.O.
- Handling Manure **SINCE 1960**
- **CUSTOM BUILT** For Special Applications



TIRE OPTIONS

- 16.5L X 16.1 New Implement Tires
- 18 X 22.5 Used Truck Tires
- 21.5L X 16.1 New Implement Tires
- 18.4 X 26 New Implement Tires
- 28L X 26 New Turf Tires
- 28L X 26 Radials
- 30.5L X 32 New Turf Tires
- 35.5L X 32 New Turf Tires
- 30.5L X 32 Radials



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2,
Alma, Ontario Canada N0B 1A0

www.huskyfarm.ca

Phone (519) 846 - 5329 Fax (519) 846 - 9378

1-800-349-1122



OPTIONS

- Spreading pattern up to 60 ft
- Discharge height 135" optional 4 ft
- Walking tandem Axle
- Single Axle
- PTO Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T
- 1000 RPM or 540 RPM
- Hydraulic drive
- Tank ends Flanged and reinforced
- Light kit (brake & tail) Standard
- Seams welded solid inside
- Tank shell thickness 3/16"
- High strength steel
- Butterfly Lid



CUT OUTS

- Clean Out
- Camel Hump
- Sight Gauge
- Slide Lid
- Pipe Down The Back
- Square Man Way
- Steering
- In tank Agitation
- Valves
- Truck Mounts
- Anti Syphon
- Paint primer Aluminized epoxy acid resistant
- Paint finish coat Urethane acid resistant
- Size of discharge 6" 8"
- Unloading speed 8" discharge up to 3600 gallon per minute adjustable
- Unloading speed 6" discharge up to 2400 gallon per minute adjustable

SOIL INJECTORS



FULL Baffles IN EVERY TANK



SWING AWAY FAN



DEALER