



HUSKY 12000 ELITE

3000 US Gal., 2500 CDN Gal., 12000 Litres



21.5L x 16.1, 10 Ply Tandem

28L x 26, 12 Ply Single Axle

Compaction	1844 sq. in. on ground	1872 sq. in. on ground @ 24 PSI
Overall height	111" (2819 mm)	109" (2768 mm)
Overall width	122.5" (3111 mm)	144" (3657 mm)
Tire pressure	35 lbs	24 lbs
Tire type	Rib implement type	Knobby turf type
Axle capacity	64000 lbs	37000 lbs
Axle width flange to flange ..	100"	113.87", 2892 mm straight axle
Empty	6,730 lbs (3,059 kg)	5,900 lbs (2,676 kg)
Loaded	31,720 lbs (14,418 kg)	35,900 lbs (15,876 kg)

- 86" (2184 mm) X 62" (1154 mm) X 14 ft (4.27 m)
- Flanged and reinforced ends welded inside and out
- 3/16" (4.5 mm) shell
- 1 full baffle
- U shaped sills, 1/4", Total contact tank to sill area 6 square ft
- Tongue is 73 inches long 4"x 8" boxed tubing 1/4" material
- Single or double, height adjustable and weight adjustable, 5000 lbs Tongue jack
- 540-1000 Optional Pto Unloading pump 4 blade
- Double lip seal, grease purgeable Roller Bearings
- Constant velocity PTO shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T
- Hydraulic Drive Optional
- 6" unloading up to 2400 gallon per minute adjustable, Up to 60 Ft wide
- Full Baffle In All Tanks
- 8" unloading up to 3600 gallon per minute adjustable, Up to 40 Ft wide
- 10 ft Discharge height, Optional 4 ft low pattern 25 Ft wide
- 10 bolt Hub, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable, 4" spindle C1045
- 5 year unconditional axle warranty (non commercial)
- Light kit (brake & tail) Standard
- Steam cleaned with phosphate before painting
- Aluminized epoxy Inside coating
- Epoxy primer & Urethane finish coat

