



# Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0  
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122



## HUSKY 23000 ELITE

**6000 US Gal., 5000 CDN Gal., 23000 Litres**

**28L x 26, 12 Ply    30.5L x 32, 12 Ply**

Compaction	3744 sq. in. on ground	4508 sq. in. on ground w/ 3" penetration
Overall height	120"	125"
Overall width	163"	163"
Discharge height	136", optional 4 ft	141" optional 4 ft
Empty	16,537 lbs (7,516 kg)	16,960 lbs (7,693 kg)
Loaded	66,517 lbs (30,235 kg)	66,940 lbs (30,364 kg)
Tire pressure	24 lbs	
Tire type	Turf type, knobby tread	
Tank width	100"	
Tank height	78"	
Tank length	19.25 ft	
Tank ends	Flanged and reinforced	
Tank shell thickness	1/4"	
Number of baffles	2 full baffles	
Inside coating	Aluminized epoxy	
Seams welded solid inside	Yes	
Sill style & thickness	U shape, 1/2" material	
Padding - sills to tank contact	9.75 square ft	
Tongue length	73"	
Tongue type and thickness	Rectangular tubing 3/8"	
Hitch	Single, Double, Swivel	
Tongue jack	8000 lbs	
Unloading pump	Fan type with high efficiency blades	
RPM	1000, optional 540 RPM	
Bearings	Timken taper, grease filled chamber	
Seals	Double seals, purgeable	
PTO	Bondioli, constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T	
Hydraulic drive	Optional	
Size of discharge	6", 8" optional	
Unloading speed 6" discharge	Up to 2400 gallon per minute adjustable	
Unloading speed 8" discharge	Up to 3600 gallon per minute adjustable	
Spreading pattern	Up to 60 ft	
Axle type	Walking tandem	
Axle weight (less tires)	4432 lbs, 2010 kg	
Axle capacity	100,000 lbs, 45,360 kg	
Axle warranty	5 year (non commercial)	
Light kit ( brake & tail)	Standard	
Axle spindle size & material	5 1/2" stress proof slid in 6 1/2" sleeve	
Hub bolt pattern	10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub greaseable	
Painting preparation	Steamed with phosphate	
Paint primer	Aluminized epoxy	
Paint finish coat	Urethane	

