



# Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0  
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122



## HUSKY 28000 ELITE

**7400 US Gal., 6000 CDN Gal., 28000 Litres**

**30.5L x 32, 12 Ply**

**35.5L x 32, 20 Ply**

|                                 |   |                         |
|---------------------------------|---|-------------------------|
| Compaction                      | 4508 sq. in. on ground  | 6446 sq. in. on ground  |
| Tire pressure                   | 24 lbs  | 28 PSI                  |
| Tire type                       | Turf type, knobby tread   | Turf type, knobby tread |
| Overall height                  | 125"  | 141                     |
| Overall width                   | 163"  | 133                     |
| Empty                           | 18,834 lbs (8560 kg)  | 17,500 lbs (7,936 kg)   |
| Loaded                          | 80,476 lbs (36,580 kg)  | 67,500 lbs (30,612 kg)  |
| Tank width                      | 100"  |                         |
| Tank height                     | 78"   |                         |
| Tank length                     | 23 ft   |                         |
| Tank ends                       | Flanged and reinforced  |                         |
| Tank shell thickness            | 1/4"  |                         |
| Number of baffles               | 2 full baffles  |                         |
| Inside coating                  | Aluminized epoxy  |                         |
| Light kit ( brake & tail)       | Standard  |                         |
| Seams welded solid inside       | Yes   |                         |
| Sill style & thickness          | U shape, 1/2" material  |                         |
| Padding - sills to tank contact | 11.5 square ft  |                         |
| Tongue length                   | 73"   |                         |
| Tongue type and thickness       | 4" x 8" rect. tubing 3/8"                                       |                         |
| Hitch                           | Single, Double, Swivel  |                         |
| Tongue jack                     | 8000 lbs  |                         |
| Unloading pump                  | Fan type with high efficiency blades                            |                         |
| RPM                             | 1000, optional 540 RPM  |                         |
| Bearings                        | Timken taper, grease filled chamber                             |                         |
| Seals                           | Double seals, purgeable   |                         |
| PTO                             | Bondioli, constant velocity, shear protected                    |                         |
| Hydraulic Drive                 | Optional  |                         |
| Size of discharge               | 6", 8" optional   |                         |
| Unloading speed 6" discharge    | Up to 2400 gallon per minute adjustable                         |                         |
| Unloading speed 8" discharge    | Up to 3600 gallon per minute adjustable                         |                         |
| Spreading pattern               | Up to 60 ft   |                         |
| Discharge height                | 10 ft optional 4 ft   |                         |
| Axle type                       | Walking tandem  |                         |
| Axle weight (less tires)        | 4432 lbs  |                         |
| Axle capacity                   | 100,000 lbs   |                         |
| Axle warranty                   | 5 year (non commercial)   |                         |
| Axle spindle size & material    | 5 1/2" stress proof slid in 6 1/2" sleeve                       |                         |
| Hub bolt pattern                | 10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub greaseable |                         |
| Painting preparation            | Steamed with phosphate  |                         |
| Paint primer                    | Epoxy   |                         |
| Paint finish coat               | Urethane  |                         |

