



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0

Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122



HUSKY 28000 SLIM LINE

7400 US Gal., 6000 CDN Gal., 28000 Litres

30.5L x 32, 12 Ply

35.5L x 32 20 Ply

Compaction	4508 sq. in. on ground	6446 sq. in. on ground
Tire pressure	26/30 lbs	28 PSI
Tire type	Turf type, knobby tread	Turf type, knobby tread
Overall height	135"	141
Overall width	131"	133
Empty	18,834 lbs (8,560 kg)	17,500 lbs (7,936 kg)
Loaded	80,500 lbs (36,600 kg)	67,500 lbs (30,612 kg)
Tank width	101"	
Tank height	95"	
Tank length	24 ft	
Tank ends	Flanged and reinforced	
Tank shell thickness	1/4" high strength steel	
Number of baffles	2 full baffles	
Inside coating	Aluminized epoxy	
Light kit (brake & tail)	Standard	
Seams welded solid inside	Yes	
Sill style & thickness	U shape, 1/2" material	
Padding - sills to tank contact	12 square ft	
Distance sills apart	54"	
Tongue length	75"	
Tongue type and thickness	4" x 8" rect. tubing 3/8"	
Hitch	Single, Double, Swivel	
Tongue jack	8000 lbs	
Unloading pump	Fan with high efficiency blades	
RPM	1000, optional 540 RPM	
Hydraulic drive	Optional	
Bearings	Timken taper, grease filled chamber	
Seals	Double seals, purgeable	
PTO	Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T	
Hydraulic drive	Optional	
Size of discharge	6", 8" optional	
Unloading speed 6" discharge	Up to 2400 gallon per minute adjustable	
Unloading speed 8" discharge	Up to 3600 gallon per minute adjustable	
Spreading pattern	Up to 60 ft	
Discharge height	135" optional 4 ft	
Axle type	Walking tandem	
Axle weight (less tires)	4432 lbs, 2009 kg	
Axle capacity	100,000 lbs, 45,351 kg	
Axle warranty	5 year (non commercial)	
Axle spindle size & material	5 1/2" stress proof HT SR slid in 6 1/2" sleeve	
Hub bolt pattern	10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub g	
Painting preparation	Steamed with phosphate	
Paint primer	Aluminized epoxy acid resistant	
Paint finish coat	Urethane acid resistant	

