



# HUSKY 7000 ELITE

1800 US Gal., 1500 CDN Gal., 7000 Litres

## 16.5L x 16.1, 10 Ply

Compaction	1208 sq. in. on ground
Tire pressure	35 PSI
Tire type	Rib implement type
Overall height	94 " (2387 mm)
Overall width	97.75" (2482 mm)
Tank width	60" (2184 mm)
Tank height	60" (2184 mm)
Tank length	12 ft (3.66 m)
Tank ends	Flanged
Tank shell thickness	3/16" (4.5 mm)
Number of baffles	1
Inside coating	Aluminized epoxy
Seams welded solid inside	Yes
Sill style & thickness	U shape, 1/4"
Padding to tank contact	6 square ft
Tongue length	55 inches
Tongue type and thickness	4" x 8" boxed tubing 3/16" material
Hitch	Single or double, height adjustable
Tongue jack	5000 lbs
Draw bar weight	Adjustable
Unloading pump	4 blade fan type
RPM	540-1000 optional
Bearings	Tapered roller
Seals	Double lip grease purgeable
PTO	Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T
Hydraulic drive	Optional
Size of discharge	6", 8" optional
Unloading speed 6" discharge	Up to 2400 gallon per minute adjustable
Spreading pattern	Up to 60 ft, 18 m
Discharge height	106", 2692 mm optional 4 ft
Axle type	Walking tandem
Axle capacity	32000 lbs
Axle spindle size & material type	2 3/4" SPS Stress proof material
Hub bolt pattern	8 bolt, 8" bolt circle, 6" pilot hole
Axle width hub flange to hub flange	Straight axle 82.25"
Hub greaseable	No
Axle warranty	5 year unconditional
Light kit ( brake & tail)	Standard
Painting preparation	Steamed with phosphate
Paint primer	Epoxy
Paint finish coat	Urethane
Empty	4,550 lbs (2,063 kg)
Loaded	17,045 lbs (7,731 kg)

