



HUSKY 9000 ELITE

2400 US Gal., 2000 CDN Gal., 9000 Litres

16.5L x 16.1, 10 Ply

21.5L x 16.1, 10 Ply

| | | |
|------------------------------------|--|------------------------|
| Compaction | 1208 sq. in. on ground | 1844 sq. in. on ground |
| Overall height | 92 " (2337 mm) | 93.75 " (2381 mm) |
| Overall width | 97.75" (2482 mm) | 103.25." (2622 mm) |
| Discharge height | 106" 2692 mm | 107.75" 2737 mm |
| Optional Discharge height | 4 ft Low Spread | 4 ft Low Spread |
| Empty | 5,354 lbs (2,433 kg) | 5,670 lbs (2,577 kg) |
| Loaded | 25,350 lbs (11,522 kg) | 25,662 lbs (11,664 kg) |
| Tank Width | 74" (1879 mm) | |
| Tank Height | 58" (1473 mm) | |
| Tank Length | 14 ft (4.32m) | |
| Tank ends | Flanged | |
| Tank shell thickness | 3/16" (4.5 mm) | |
| Number of baffles | 1 | |
| Tire pressure | 35 PSI | |
| Tire type | Rib implement type | |
| Seams welded solid inside | Yes | |
| Sill style & thickness | U shape, 1/4" | |
| Padding to tank contact | 6 square ft | |
| Tongue length | 55 inches | |
| Tongue type and thickness | 4"x 8" boxed tubing 3/16" material | |
| Hitch | Single or double, height adjustable | |
| Tongue jack | 5000 lbs | |
| Draw bar weight | Adjustable | |
| Unloading pump | 4 Blade fan type | |
| RPM | 540-1000 optional | |
| Bearings | Tapered roller | |
| Seals | Double lip grease purgeable | |
| Pto | Constant velocity shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T | |
| Hydraulic drive | Optional | |
| Size of discharge | 6", 8" optional | |
| Unloading speed 6" discharge | Up to 2400 gallon per minute adjustable | |
| Unloading speed 8" discharge | Up to 3600 gallon per minute adjustable | |
| Spreading pattern | Up to 60 ft, 18 m | |
| Axle type | Walking tandem | |
| Axle capacity | 32000 lbs | |
| Axle spindle size & material | 2 3/4" SPS stress proof material | |
| Hub bolt pattern | 8 bolt, 8" bolt circle, 6" pilot hole | |
| Axle width flange to flange | Straight axle 82.25" | |
| Hub greaseable | No | |
| Axle warranty | 5 year unconditional (non commercial) | |
| Light kit (brake & tail) | Standard | |
| Inside coating | Aluminized epoxy | |
| Painting preparation | Steamed with phosphate | |
| Paint primer | Epoxy | |
| Paint finish coat | Urethane | |

