



H10000 PUMP

This Pump is manufactured for the larger pits and commercial farmers. The drive shaft tube and the stand pipe tube for manure are made of 1/4" steel. The main inlet housing is made from 3/8 plate and from a wear hardened steel to with stand extra duty use. The turn motor is a larger motor with more torque.

Pit Depth **8 Ft** **10 ft** **12 Ft** **other lengths also**

- Overall Length 139" (3530 MM) 163" (4140 MM) 187" (4750 MM)
- Max. Pit Depth 8 Ft. 10" 10 Ft. 10" 12 Ft. 10"
- Top agitation spout from floor 72" 96" 120"
- Style 2 point hitch
- HP Required @1.1 box 170
- PTO 1000 RPM Shear Protected
- Pipe Size 10" (254 MM)
- PTO 1000 RPM Shear Protected
- Length of Discharge Pipe 20 Ft (6 M) Length Optional
- Agitator Swivel 300 degrees
- Agitating Spouts 2
- Vertical Deflector Optional 8" Diameter
- Top Cone outlet size 4" (101 MM)
- Bottom spout from floor 24"
- Bottom Cone Outlet size 7" (152 MM)
- Inlet Hole 12" (304 MM)
- Housing Size 23" x 34" (584x863)
- Impeller Hi Efficiency 4 blade
- Impeller size 18" (457 MM)
- Trailer Tilting Hyd. Cylinder
- Controls Hydraulic
- Approximate Pump Volume . 10,000 GPM
- Discharge Support Legs 12 Ft.
- Discharge Pipe Cart Optional 10"

